



MQS

TE Internal #: 1-1670990-1
10 Position Housing, Housing for Female Terminals, Wire-to-Board,
2.5 mm [.098 in] Centerline, Black, Wire & Cable, Signal, Cable
Mount (Free-Hanging)

[View on TE.com >](#)

Automotive Parts > Automotive Connectors > Automotive Housings > MQS, CONNECTOR HOUSING



Number of Positions: 10
Connector & Housing Type: Housing for Female Terminals
Mating Tab Width: .63 mm [.025 in]
Connector System: Wire-to-Board
Centerline (Pitch): 2.5 mm [.098 in]

[All MQS, CONNECTOR HOUSING \(338\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Board
Sealable	No
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	10
Number of Rows	2

Electrical Characteristics

Operating Voltage	12 VDC
-------------------	--------



Body Features

Cable Exit Angle	90°
Primary Product Color	Black
Connector & Keying Code	A

Contact Features

Contact Size	.63mm
Contact Type	Receptacle
Mating Tab Width	.63 mm[.025 in]
Contact Current Rating (Max)	7.5 A

Mechanical Attachment

Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF10
Centerline (Pitch)	2.5 mm[.098 in]

Dimensions

Product Width	8.7 mm[.342 in]
Row-to-Row Spacing	2.54 mm[.1 in]
Product Length	19.9 mm[.783 in]
Connector Height	18.5 mm[.728 in]

Usage Conditions

Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]

Operation/Application

Conforms to Automation Guideline	Yes, KOMAX Guideline for automatic component insertion for electrical connections, Version 5.0 (March 2018)
Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------



Packaging Features

Packaging Method	Bulk
Packaging Quantity	1000

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-M8793-T273
MQS, RECEPTACLE AND TAB



TE Part # 969587-1
MOD2 PIN HEADER 2X5P



TE Part # 969587-2
MOD2 STIFTELEIS2X5P

Customers Also Bought



TE Part #1379671-5
40W PLUG HSG ASSY NATURAL



TE Part #1-1418507-2
SOCKET HSG 4POS.,AMP MCP2.8 /MCP6.3K



TE Part #1813271-3
SEALED MT2 PLUG HOUSING ASSEMBLY



TE Part #4-1879073-7
THS10 4K7 5%



TE Part #1-2035077-3
PLUG HSG, 4 POSN HYBRID 0.64/2



TE Part #1-2203769-3
2POS, MCON 1.2 CB REC 1p TL SEALED




TE Part #2287871-2
24POS,MIXED,TAB HSG,025,090, CODE B,ASSY



TE Part #2005510-2
SQUIB AK2 PLUG HSG1



TE Part #2434829-1
2POS,MT 2,REC HSG,COD A



TE Part #2435082-2
MT 2,TERMINAL,SRC SN

Documents

Product Drawings
10POS MQS REC COD A
English

CAD Files
3D PDF
3D
Customer View Model
ENG_CVM_CVM_1-1670990-1_A_c-1-1670990-1-a.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_1-1670990-1_A_c-1-1670990-1-a.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1-1670990-1_A_c-1-1670990-1-a.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English