


Rectifier diodes general purpose

BY249 series

FEATURES

- Low forward volt drop
- High thermal cycling performance
- Low thermal resistance

SYMBOL



QUICK REFERENCE DATA

$V_R = 300\text{ V} / 600\text{ V} / 800\text{ V}$
$V_F \leq 1.05\text{ V}$
$I_{F(AV)} = 7\text{ A}$
$I_{FSM} \leq 60\text{ A}$

GENERAL DESCRIPTION


Glass-passivated double diffused rectifier diodes. The devices are intended for low frequency power rectifier applications.

The BY249 series is supplied in the conventional leaded SOD59 (TO220AC) package.

PINNING

PIN	DESCRIPTION
1	cathode
2	anode
tab	cathode

SOD59 (TO220AC)



LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.UNIT			UNIT
				-300	-600	-800	
V_{RSM}	Peak non-repetitive reverse voltage	BY249	-	300	600	800	V
V_{RRM}	Peak repetitive reverse voltage		-	300	600	800	V
V_{RWM}	Crest working reverse voltage		-	200	500	700	V
V_R	Continuous reverse voltage		-	200	500	700	V
$I_{F(AV)}$	Average forward current ¹	sinusoidal; $a = 1.57$; $T_{mb} \leq 131\text{ }^\circ\text{C}$	-	7			A
$I_{F(RMS)}$	RMS forward current	sinusoidal; $a = 1.57$;	-	11			A
I_{FRM}	Peak repetitive forward current		-	60			A
I_{FSM}	Peak non-repetitive forward current.		$t = 10\text{ ms}$	-	60		
		$t = 8.3\text{ ms}$	-	66			A
		sinusoidal; $T_j = 150\text{ }^\circ\text{C}$ prior to surge; with reapplied $V_{RWM(max)}$					
I^2t	I^2t for fusing	$t = 10\text{ ms}$	-	18			A ² s
T_{stg}	Storage temperature		-40	150			$^\circ\text{C}$
T_j	Operating junction temperature		-	150			$^\circ\text{C}$

¹ Neglecting switching and reverse current losses.

 Rectifier diodes
 general purpose

BY249 series

THERMAL RESISTANCES






SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th\ j-mb}$	Thermal resistance junction to mounting base	in free air.	-	-	2.0	K/W
$R_{th\ j-a}$	Thermal resistance junction to ambient		-	60	-	K/W

STATIC CHARACTERISTICS $T_j = 25\text{ °C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_F	Forward voltage	$I_F = 20\text{ A}$	-	1.2	1.6	V
I_R	Reverse current	$I_F = 5\text{ A}; T_j = 100\text{ °C}$	-	0.9	1.05	V
		$V_R = V_{RWM}; T_j = 125\text{ °C}$	-	0.1	0.4	mA

Rectifier diodes
general purpose


BY249 series



Rectifier diodes
general purpose

BY249 series

MECHANICAL DATA



Notes

1. Refer to mounting instructions for TO220 envelopes.
2. Epoxy meets UL94 V0 at 1/8".

**Rectifier diodes
general purpose**

BY249 series**DEFINITIONS**

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	
♥ Philips Electronics N.V. 1998	
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.	
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.